

The Quickie XTR "Xtreme Terrain Reflex" is the first monoshock suspension chair on the market. The Quickie XTR features Rock Shox®, a unique suspension system developed exclusively for Quickie. This system offers superior performance with factory-tuned rebound and compression, as well as better side to side stability. With the Quickie XTR the rider is assured a smooth, stable ride over a variety of terrain.

Quickie®
XTR



Mountain Tire Package

The Quickie XTR mountain tire package includes tires designed for a multitude of "xtreme" terrain. Both the heat treated and mountain tires are 24" in height, which make it easy to change wheels without having to re-adjust the chair.



Angle-adjustable Folding Backrest

The back and seat frames are attached together to facilitate seat-to-back angles and to accommodate posturing and positioning devices. The backrest can be folded completely for easy, compact transport.



Rock Shox® Monoshock Suspension

This unique suspension system provides a smoother ride up curbs and on uneven terrain, reducing back pain and fatigue. Rock Shox® has 2.5" rear wheel travel for shock absorption providing the rider with a more controlled and confident ride.



Quickie® Rigid Series



Quickie Ti Titanium
LIGHTEST WEIGHT



Quickie XTR
SUSPENSION



Quickie R2 Adjustable
QUICK CAMBER ADJUSTMENT



Quickie R2 Rigid



Quickie ST/DT*
CHROME-MOLY FRAME



Quickie GPV Comp



Quickie GPV Ti

CLASSIC GP SERIES



Quickie GPV



Quickie GP SA

*Also available in ped. sizes.

Quickie Ti Titanium

Configuration Ranges		
Seat Width	13" - 18"	1" increments
Seat Depth	14" - 19"	1" increments
Front Frame Angle	70°, 80°, 85°	
Frame Inset	0", 1", 2"	
Titanium Backrest	10" - 15"	1" increments
Aluminum Backrest	11" - 20"	1" increments
Caster Sizes	3", 4", 5"	
Rear Wheels	24", 25", 26"	
Rear Wheel Spacing	0.75" - 1.5"	0.25" increments
Center of Gravity	0.5" - 4.5"	0.5" increments
Camber	0°, 2°, 4°, 8°	

Front Seat Height 0.5" increments	Rear Seat Height 0.5" increments	Footrest Adjustability Range (from sling - without cushion)
16	15" - 12.5"	13.25" - 11.25"
16.5"	15.5" - 13"	13.75" - 11.75"
17"	16" - 13.5"	14.25" - 11.25"
17.5"	16.5" - 14"	14.75" - 11.75"
18"	17" - 14.5"	15.25" - 12.25"
18.5"	17.5" - 15"	15.75" - 12.75"
19"	18" - 15.5"	16.25" - 13.25"
19.5"	18.5" - 16"	16.75" - 13.75"
20"	19" - 16.5"	17.25" - 14.25"

Quickie R2 Rigid/Quickie R2 Adjustable

FRONT SEAT HEIGHT CASTER OPTIONS	3" MICROS 3 1/4" FORK	3" MICROS 4 1/4" FORK	4" CASTERS 4 3/4" FORK	4" CASTERS 3 1/4" FORK	5" CASTERS 4 3/4" FORK		
FRAME							
Short	18"	18 1/4"	18 1/2"	18 1/2"	18 1/2"		
Regular	19"	19 1/4"	19 1/2"	19 1/2"	19 1/2"		
Tall	20"	20 1/4"	20 1/2"	20 1/2"	20 1/2"		
OVERALL CHAIR WIDTH SEAT WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL CHAIR WIDTH- 3"	22 1/2"	23 1/4"	24 1/8"	25 1/4"	26 1/4"	27 1/4"	28 1/4"
OVERALL CHAIR WIDTH- 12"	28 1/8"	29 1/4"	30 1/4"	31 1/4"	32 1/4"	33 1/4"	34 1/4"

* sizes may vary 0/12 camber insert
WEIGHT: 22 1/2 lbs. WEIGHT CAPACITY: 250 lbs.

Quickie XTR

	0 Degree Camber Tube Front Seat Height	Rear Seat Height	4 Degree Camber Tube Front Seat Height	Rear Seat Height	8 Degree Camber Tube* Front Seat Height	Rear Seat Height
14" Depth	18 3/4"	17"	18 3/4"	16 1/2"	18 3/4"	16"
15" Depth	19"	17"	19"	16 1/2"	18 3/4"	16"
16" Depth	19"	17"	19"	16 1/2"	18 3/4"	16"
17" Depth	19 1/4"	17"	19 1/4"	16 1/2"	18 3/4"	16"
18" Depth	19 1/4"	17"	19 1/4"	16 1/2"	18 3/4"	16"

* with 8° camber, caster is mounted in upper hole set ** rounded to nearest 1/4"

FRAME	WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH	24"	25"	26"	27"	28"	29"	30"	

* based on 0° camber
WEIGHT: 23 1/2 lbs. WEIGHT CAPACITY: 250 lbs.

Quickie ST/DT

FRONT SEAT HEIGHT (Based on 5" caster /24" rear wheel with 4° camber)								
STANDARD	SMALL STD	LARGE STD	STEEP	TALL	ULTRA TALL			
19"	17 1/2"	20 3/8"	20"	20"	20"			
REAR SEAT HEIGHT (Based on 5" caster /24" rear wheel with 4° camber)								
STANDARD	SMALL STD	LARGE STD	STEEP	TALL	ULTRA TALL			
15 1/2"	13 3/8"	16"	14 1/2"	17 1/2"	19 3/4"			
FRAME	WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH	24"	25"	26"	27"	28"	29"	30"	

* based on 0° camber
WEIGHT: 27 lbs. WEIGHT CAPACITY: 250 lbs.
* heights may vary 1/8"

*All specifications are subject to change with each configuration.

For more information on the Quickie Rigid Series chairs and other products offered by Sunrise Medical visit:
www.sunrisemedical.com

Quickie GPV

FRONT SEAT HEIGHT (For Standard Frames Only)									
CASTER OPTIONS	3" MICROS 6" FORK		5" LP POLY 5 1/4" FORK		6" PNEU 5 1/4" FORK		6" POLY 5 1/4" FORK		
CASTER FORK MOUNTING HOLE									
TOP	17 7/8"		17 3/16"		17 3/4"		17 5/8"		
BOTTOM	18 3/8"		18 3/16"		18 3/4"		18 5/8"		
REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)									
REAR WHEEL	22"	24"	24"	24"	24" HT	26"	26" HT	26"	26"
	PNEU	LATEX TUBULAR	HP CLNCHR	PNEU	TEN/B-BALL TURBO TRD	LATEX/PNEU HP/CLNCHR	TEN/B-BALL TURBO TRD	PNEU	TEN/B-BALL TURBO TRD
AXLE/HOLE POSITION									
TOP	15 3/4"	15 7/8"	16"	16 1/8"	16 1/4"	16 3/8"	17 1/4"	17 5/8"	17 5/8"
MIDDLE	16"	16"	16 5/8"	16 3/4"	16 7/8"	17 1/2"	17 7/8"	18 1/4"	18 1/4"
BOTTOM	16 5/8"	17 1/8"	17 1/4"	17 3/8"	17 1/2"	18 1/8"	18 1/2"	18 7/8"	18 7/8"
FRAME WIDTH									
	12"	13"	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)									
	23"	24"	25"	26"	27"	28"	29"	30"	31"
WEIGHT: 21 1/2 lbs. (w/steel rear axles) 19 3/4 lbs. (w/titanium rear axles)									

WEIGHT CAPACITY: 250 lbs.

Quickie GPV Competition

FRONT SEAT HEIGHT (For Standard Frames Only)							
CASTER OPTIONS	3" MICROS 6" FORK		5" LP POLY 5 1/4" FORK				
CASTER FORK MOUNTING HOLE							
TOP	17 7/8"		17 3/16"				
BOTTOM	18 3/8"		18 3/16"				
REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)							
REAR WHEEL	24"	24"	24"	24" HT	26"	26" HT	26"
	LATEX TUBULAR	HP CLNCHR	PNEU	TEN/B-BALL TURBO TRD	LATEX/PNEU HP/CLNCHR	TEN/B-BALL TURBO TRD	PNEU
AXLE/HOLE POSITION							
TOP	15 7/8"	16"	16 1/8"	16 1/4"	16 3/8"	17 1/4"	17 5/8"
MIDDLE	16"	16 5/8"	16 3/4"	16 7/8"	17 1/2"	17 7/8"	18 1/4"
BOTTOM	17 1/8"	17 1/4"	17 3/8"	17 1/2"	18 1/8"	18 1/2"	18 7/8"
FRAME WIDTH							
	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)							
	25"	26"	27"	28"	29"	30"	31"
WEIGHT: 21 1/2 lbs. (w/steel rear axles) 19 3/4 lbs. (w/titanium rear axles)							

WEIGHT CAPACITY: 250 lbs.

Quickie GP Swing-away

FRONT SEAT HEIGHT (For Standard Frames Only)									
CASTER OPTIONS	5" LP POLY 5 1/4" FORK		6" PNEU 5 1/4" FORK		6" POLY 5 1/4" FORK				
CASTER FORK MOUNTING HOLE									
TOP	15 5/16"		16 1/8"		16"				
BOTTOM	16 5/16"		17 1/8"		17"				
REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)									
REAR WHEEL	22"	24"	24"	24" HT	26"	26" HT			
	PNEU	LATEX TUBULAR	HP CLNCHR	PNEU	TEN/B-BALL TURBO TRD	LATEX/ HP/CLNCHR			
AXLE/HOLE POSITION									
TOP	15 7/8"	16 3/8"	16 1/2"	16 5/8"	16 3/4"	17 3/8"			
MIDDLE	16 1/2"	17"	17 1/8"	17 1/4"	17 3/4"	18"			
BOTTOM	17 1/8"	17 5/8"	17 3/4"	17 5/8"	18"	18 3/8"			
FRAME WIDTH									
	12"	13"	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)									
	22 1/2"	23 1/2"	24 1/2"	25 1/2"	26 1/2"	27 1/2"	28 1/2"	29 1/2"	30 1/2"
WEIGHT: 24 1/2 lbs. WEIGHT CAPACITY: 250 lbs.									

Quickie GPV Titanium

FRONT SEAT HEIGHT (For Standard Frames Only)									
CASTER OPTIONS	3" MICROS 6" FORK		5" LP POLY 6" FORK		6" PNEU 6" FORK		6" POLY 5 1/4" FORK		
CASTER FORK MOUNTING HOLE									
TOP	17 7/8"		18"		18 5/16"		18 3/16"		
BOTTOM	18 3/8"		19"		19 5/16"		19 3/16"		
REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)									
REAR WHEEL	22"	24"	24"	24" HT	26"	26" HT	26"	26"	26"
	PNEU	LATEX TUBULAR	HP CLNCHR	PNEU	TEN/B-BALL TURBO TRD	LATEX/ HP/CLNCHR	PNEU	TEN/B-BALL TURBO TRD	PNEU
AXLE/HOLE POSITION									
TOP	15 3/8"	15 7/8"	16"	16 1/8"	16 1/4"	16 3/8"	17 1/4"	17 5/8"	17 5/8"
MIDDLE	16"	16 1/2"	16 5/8"	16 3/4"	16 7/8"	17 1/2"	17 7/8"	18 1/4"	18 1/4"
BOTTOM	16 5/8"	17 1/8"	17 1/4"	17 3/8"	17 1/2"	18 1/8"	18 1/2"	18 7/8"	18 7/8"
FRAME WIDTH									
	14"	15"	16"	17"	18"	19"	20"		
OVERALL WIDTH (With Standard Camber and No Armrests)									
	25"	26"	27"	28"	29"	30"	31"		
WEIGHT: 18 lbs. WEIGHT CAPACITY: 250 lbs.									